

1 Dimensions: 23 5/8" (60 cm), 47 1/4" (120 cm). Components: topboard, baseboard. Thicknesses: 3 mm (3/32"), 4 mm (5/32"), 7 mm (9/32").

2 Environmental conditions: 24h, 45%-65% humidity, 18°C (65°F). Prohibited: No moisture, no heat.

3 Humidity: RH < 75%. * sand cement screed 2%, * wooden floor 10%, * anhydrite 0,5%.

4 Check for unevenness: 1 meter straightedge, max. 3 mm deviation.

5 Apply Unifloor PE-foil 150 µm (4 mil) and Unifloor alutape. Dimensions: 1 15/16" (50 mm), 12", 200 mm.

6 Prepare the base surface.

7 Cut the base material.

8 Lay the base material.

9 Install side strip. Dimensions: 3/8", 10 mm.

10 Lay the base material. Dimensions: 47 1/4" (120 cm), 30 cm, 11 13/13".

11 Lay the base material. Dimensions: 47 1/4" (120 cm), 35 7/16" (90 cm), 30 cm, 11 13/13".

12 Lay the base material. Dimensions: 35 7/16" (90 cm), 47 1/4" (120 cm), 11 13/13", 30 cm, 60 cm, 23 5/8".

13 Lay the topboard. Dimensions: 47 1/4" (120 cm), 35 7/16" (90 cm), 23 5/8" (60 cm), 30 cm, 11 13/13".

14 Lay the topboard. Prohibited: No moisture, no heat.

15 Lay the topboard. Dimensions: 47 1/4" (120 cm), 23 5/8" (60 cm), 60 cm, 60 cm.

16 Lay the topboard. Dimensions: 47 1/4" (120 cm), 23 5/8" (60 cm). Follow sequence!

17 Lay the topboard. Use 120 grain sand paper.

18 Lay the topboard. Dimensions: 33", max. 10 m, 5/8" (16 mm). Expansion joints.

19 Lay the topboard. Dimensions: 5/8" (16 mm). Expansion joints between rooms.

20 Lay the topboard. Heat-foil.

21 Lay the topboard. Unifloor PE-foil 200 µm (6 mil), Heat-blok.

22 Lay the topboard. Dimensions: < 48h, 3/8", 10 mm.

Unifloor Underlay Systems
Arnsbergstraat 4
7418 EZ Deventer - The Netherlands
T +31 (0) 570 85 55 33
E info@unifloor.nl

UK Toll Free 0845 603 0 906


Service-Line für Deutschland, Österreich & Schweiz:
T +49 (152) 264 111 11



- ◆ Fast track subfloor preparation for when time is an issue
- ◆ Exceptionally stable free floating underlay system
- ◆ Superb smooth finish, ready for floor covering
- ◆ Instant floor levelling of most substrates
- ◆ Overcomes many substrate problems
- ◆ For the immediate glue-down of vinyl, linoleum, cork, rubber, carpet, etc.
- ◆ Quick and easy to fit and to handle (pack sizes)



FITTING INSTRUCTION FILM



uniFloor
UNDERLAY SYSTEMS BV

Unifloor Underlay Systems
Arnsbergstraat 4
7418 EZ Deventer - The Netherlands
T +31 (0) 570 85 55 33
E info@unifloor.nl

UK Toll Free 0845 603 0 906

Service-Line für Deutschland,
Österreich & Schweiz:
T +49 (152) 264 111 11

www.unifloor.nl